



S092T

Intel Rocket Lake-S Platform Processor



CPU	
CPU	Intel 10/11th Rocket Lake-S, FCLGA1200
TDP	65 W
Chipset	H510

Display	
Graphic card	Intel UHD Graphics
Multi displays	Support Three displays
Interface	IO: 1 x HDMI 1.4; 1 x DP 1.2 80pin: 1xHDMI2.0

System	
Memory	Dual SoDIMM DDR4 Max. 64 GB
Storage	1 x M.2 2280, SATA/PCIE Self-adaptation
OS	Window11 /Windows10/ Linux
WatchDog	Support
Auto Power On	Yes
RTC	Yes
Power Input	12-19v 2.5/5.5 DC-In
Dimension	195mm(L) x 180mm(W) x 30mm(H)
Operating Temp.	-10~50°C
Operating Humidity	10%~90% non-condensing
Storage Temp	-20~70°C
Operating Humidity	5%~95% non-condensing

Network	
Lan IC	1x RTL8111H/ RTL8111M
Lan Interface	10/100/1000Mbps
Lan Connector	1 x RJ45 Port
Wireless Type	WIFI 6e&BT5.2 Module
Wireless Interface	M.2 Key E 2230 Module

I/O interface	
Display	1 x HDMI 1.4 1 x DP1.2
USB	3 x USB 3.2 ; 3 x USB 2.0 ;
Button	1 x PowerButton, 1 x Reset Button 1 x Recover
LAN	1 x RJ45
AUDIO	1 x Line Out ; 1 x MIC-In
POWER	1 x 2.5/5.5 DC-IN Connector
JAE	1 x JAE 80pin: HDMI2.0, 2 x USB2.0, 1 x USB3.0, TTL, 1 x Line Out

